

Drop Cable - Dielectric Flat



Dielectric Flat Drop Cable

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1-24	13-ZI0XX-04D4	4.5 x 8.0

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Dielectric Flat Drop Cable with 1F OFNR Cordage

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1	13-ZI001-04W5	4.3 x 8.0

Fiber type: 250µm G.657.A1, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Reduced-size Dielectric Flat Drop Cable

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1-12	13-ZI0XX-04M4	3.5 x 6.5

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640