

Drop Cable - Toneable Flat



Toneable Flat Drop Cable

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1-24	13-ZI0XX-0405000A	4.5 x 10.2

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Toneable Flat Drop Cable with 1F OFNR Cordage

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1	13-ZI001-04W5	4.5 x 10.2

Fiber type: 250µm G.657.A1, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Reduced-size Toneable Flat Drop Cable

Cable Fiber Count	Cablcon Standard Part Number	Dimensions (mm)
1-12	13-ZI0XX-04M4	3.5 x 8.7

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Drop Cable - Armored Central Tube



Single Jacket / Single Armor Drop Cable

Cable Fiber Count	Cablcon Standard Part Number	OD (mm)
12	13-KI012-0404	8.5
24	13-KI024-0404	9

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Single Jacket / Single Armor Drop Cable with 900µm TB

Cable Fiber Count	Cablcon Standard Part Number	OD (mm)
2	13-SI002-0404	8.2
4	13-SI004-0404	10.3
6	13-SI006-0404	10.3

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 1.35 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640