

Flat Ribbon - Loose Tube



Ribbon in Gel-Filled Loose Tube Dielectric Cable

Fiber Count		Cablcon Standard Part Number	OD (mm)
Tube	Cable		
24	96	13-EI096-04D4G	17.0
36	144	13-EI144-04D4G	18.0
48	192	13-EI192-04D4G	18.5
48	288	13-EI288-04D4G	20.0
72	432	13-EI432-04D4G	21.0
96	576	13-EI576-04D4G	22.5
144	864	13-EI864-04D4G	24.5

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating ≥ 3.0 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

Ribbon in Gel-Filled Loose Tube Single Jacket / Single Armor Cable

Fiber Count		Cablcon Standard Part Number	OD (mm)
Tube	Cable		
24	96	13-WI096-0404G	18.5
36	144	13-WI144-0404G	19.5
48	192	13-WI192-0404G	20.5
48	288	13-WI288-0404G	21.5
72	432	13-WI432-0404G	22.5
96	576	13-WI576-0404G	24.0
144	864	13-WI864-0404G	26.0

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating ≥ 3.5 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640