

Loose Tube Cable - General Purpose



General Purpose Dielectric Dry Loose Tube Cable

Fiber Count		Cablcon Standard Part Number	OD (mm)
Tube	Cable		
12	12-60	13-LI0XX-0404	10.5
12	72	13-LI072-0404	10.7
12	96	13-LI096-0404	12.3
12	144	13-LI144-0404	15.5
12	288	13-LI288-0404	18.5
24	432	13-LI432-0404	18.5

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 2.7 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640

General Purpose Single Jacket / Single Armor Dry Loose Tube Cable

Fiber Count		Cablcon Standard Part Number	OD (mm)
Tube	Cable		
12	12-60	13-KI0XX-0404	12.3
12	72	13-KI072-0404	12.8
12	96	13-KI096-0404	14.3
12	144	13-KI144-0404	17.5
12	288	13-KI288-0404	20.5
24	432	13-KI432-0404	20.5

Fiber type: 250µm G.652.D, Operating Temp. Range (°C): - 40 to + 70, Tensile rating = 2.7 kN, **Performance Standard:** Telcordia GR-20 & ICEA S-87-640