



CABLCON
AN IEWC COMPANY

VARIABLE FIBER MANAGEMENT

VFM® RACK MOUNT, WALL MOUNT
& HEAD END SOLUTIONS

IN-BUILDING RACK MOUNT HEAD END PANELS

- 1RU - 3 Adapter-Plate / Cassette capacity
- 2RU - 6 Adapter-Plate / Cassette capacity & D-rings



IN-BUILDING WALL MOUNT VFM® SYSTEM

- Wall Mount with Fiber Management Spool
- Wall Mount Slack Management
- 4 adapter plate/cassette capacity
- 12 & 24 Position MPO Cassettes



IN-BUILDING RACK MOUNT VFM® SYSTEM

- 1RU Rack Mount – Fiber Tolerance of 150' in OFNR/OFNP & 100' in Corr2Flex+® Micro Armor Cable
- 2RU Rack Mount, D-Rings – Fiber Tolerance of 300' in OFNR/OFNP & 200' in Corr2Flex+® Micro Armor Cable
- 3 & 6 Adapter-Plate / Cassette Capacity
- Wall Mount Slack Management
- 12 & 24 Position MPO cassettes



ASSOCIATED PRODUCTS

- Fixed attenuators
- Fiber optic patch cords
- Racks & enclosures
- Hardware
- RF braid jumpers
- RF ¼" & ½" JMA PIM rated jumpers
- RG Flex DC power cable






VALUE-ADD SERVICES

- Kitting
- Quick-ship
- Custom lengths with your run tolerance
- 12, 24 & 48 fiber factory terminated MPO connectors
- Cablcon Web Based Fiber Optic Test Report



TESTED TO MEET THESE STANDARDS

- Assembly & Manufacturing: ISO 9001 & TL 9000
- Telcordia GR-326-CORE I4, UL, ITU, IEC, & TIA



Wall Mount Slack Management Power Distribution



TELECOM & BROADBAND



DATA CENTERS



GRID RENEWAL



TEMPORARY POWER

