1. CONDUCTOR:

1.1 Size and Material: 14 19/.0147" AWG silver-plated copper wire.

1.2 O.D.: .069" nom.

2. INSULATION:

2.1 Extruded special ETFE (Tefzel® 750).

2.2 Wall thickness: .016" nom.

2.3 O.D.: .101" nom.

2.4 Marking on the insulation: as per UL and CSA Standards

2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

3.1 Voltage rating: 600 VAC R.M.S.
3.2 Temperature rating: 200°C


4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 10086.

4.2 CSA standard C22.2 No.210 (AWM), Class I, Group A/B.

CUSTOMER APPROVAL

Sign:		 	
Date:			



UNCONTROLLED DOCUMENT A later revision of this specification may exist.



This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

A member of The Marmon Group of companies

Done: Tain lette Date:

March 23, 2010

ph sh Date:

Scale:

Size:

March 23, 2010

1 of 1



1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

Code Ident. No:

57104

XTL16S1419/0147-X

Specification No.: F04984-X Rev.