1. CONDUCTOR:

1.1 Size and Material: 14 AWG, 19 strands, nickel-plated copper wire.

1.2 O.D.: .069" nom.

2. INSULATION:

2.1 Extruded PTFE.

2.2 Wall thickness: .013" nom.

2.3 Marking on the insulation: as per UL and CSA Standards.

2.4 O.D.: .095" ± .002"

2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:


3.1 Voltage rating: 300 VAC R.M.S.
3.2 Temperature rating: 250°C

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 1815.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign:		 	
Date:			



UNCONTROLLED DOCUMENT
A later revision of this specification may exist.



This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

The Marmon G

A member of The Marmon Group of companies

Done:

Date:

March 10, 2011

Date:

Scale:

Size:

March 10, 2011

1 of 1



1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

XE13N1419/0147-X

Code Ident. No: Specification No.: F00260-X

Rev.

Wire & Cable Specification - HBR.04.86.D