



ATLAS WIRE CORPORATION
1601 GLENLAKE AVE
ITASCA, IL 60143
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire Corporation
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#24 19/36 TC .010" PVC .003" NYLON
RoHS COMPLIANT
MIL-16878/17 TYPE BN
105c - 600 VOLTS

CONDUCTOR:	#24 19/36 TC 3/8" UNILAY NOMINAL O.D. .024" APPROXIMATE CIRCULAR MILL AREA 475 WEIGHT PER THOUSAND FEET 1.50# BASIC SPECIFICATION ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING 105c VOLTAGE RATING 600 VOLTS ELONGATION 300% AVG. SPECIFIC GRAVITY 1.34 DUROMETER (SHORE) 47 (D) TENSILE STRENGTH 3000 PSI AVG SPARK TESTED 5,700 VOLTS OXYGEN INDEX 25 BRITTLE POINT -55c FINISHED O.D. .044" WEIGHT PER 1,000 FEET 2.14#
NYLON:	ELONGATION 300% TENSILE STRENGTH 7400 PSI @ 50% RELATIVE HUMIDITY SPECIFIC GRAVITY 1.13 OVERALL DIAMETER .050" WEIGHT PER M FEET 2.338#
REVISION:	MIL-DTL-16878G - PRINT REQUIRED*

* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED
PLEASE CALL THAT OUT AT TIME OF ORDER.

MEETS ALL REQUIREMENTS LISTED ON THE MIL-DTL-16878/17B DETAIL SPECIFICATION SHEET WITH THE EXCEPTION OF ATLAS CONDITIONING FOR THE HEAT RESISTANCE TEST AT 136c.

www.atlaswirecorp.com

Revision 07/24/23