

# H05VV-F / 05VV-F



**TECHNICAL DATA**

PVC connection cable, H05VV-F acc. to DIN VDE 0285-525-2-11 / DIN EN 50525-2-11; 05VV-F in alignment with DIN VDE 0285-525-2-11 / DIN EN 50525-2-11

**Temperature range** flexible -5°C to +70°C  
fixed -40°C to +70°C

**Nominal voltage** AC U<sub>0</sub>/U 300/500 V

**Test voltage** 2000 V

**Breakdown voltage** 4000 V

**Minimum bending radius** flexible 7.5x Outer-Ø  
fixed 4x Outer-Ø

• Sheath colour: see table

**CABLE STRUCTURE**

- Copper wire bare, finely stranded acc. to DIN VDE 0295 Class 5 / IEC 60228 Class 5
- Core insulation: PVC acc. to DIN VDE 0207-363-3 / DIN EN 50363-3 (compound type T12)
- Core identification acc. to DIN VDE 0293-308, 2 - 5 core(s): colour coded  
7 core(s): black cores with consecutive labeling in white digits
- Protective conductor: starting with 3 cores,  
G = with protective conductor GN-YE,  
x = without protective conductor
- Cores stranded in layers with optimal lay lengths
- Outer sheath: PVC acc. to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1 (compound type TM2)

**PROPERTIES**

- the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

**TESTS**

- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- certifications and approvals:  
H05VV-F: HAR  
EAC

**APPLICATION**

For medium mechanical stress for use in households and offices, including damp rooms; including household appliances such as refrigerators, hoovers and washing machines.

**NOTES**

- the conductor is metrically (mm<sup>2</sup>) constructed, AWG numbers are approximated, and are for reference only

**H05VV-F**

No. cores x cross-sec. mm <sup>2</sup>	AWG, approx.	Outer-Ø min - max mm	Cu factor per km	Weight kg/km, approx.	grey	orange	black	white
					Part no.	Part no.	Part no.	Part no.
2 x 0.75	19	5.7 - 7.2	14.4	50.0	<b>30117</b>	<b>30115</b>	<b>29450</b>	<b>29451</b>
3 G 0.75	19	6.0 - 7.6	21.6	60.0	<b>30127</b>	<b>30125</b>	<b>29452</b>	<b>29453</b>
4 G 0.75	19	6.6 - 8.3	29.0	73.0	<b>30137</b>	<b>30135</b>	<b>29454</b>	<b>29455</b>
5 G 0.75	19	7.4 - 9.3	36.0	88.0	<b>30147</b>	<b>30145</b>	<b>29456</b>	<b>29457</b>
2 x 1	18	5.9 - 7.5	19.0	57.0	<b>30157</b>	<b>30155</b>	<b>29458</b>	<b>29459</b>
3 G 1	18	6.3 - 8.0	29.0	73.0	<b>30167</b>	<b>30165</b>	<b>29460</b>	<b>29461</b>
4 G 1	18	7.1 - 9.0	38.0	85.0	<b>30177</b>	<b>30175</b>	<b>29462</b>	<b>29463</b>
5 G 1	18	7.8 - 9.8	48.0	105.0	<b>30187</b>	<b>30185</b>	<b>29464</b>	<b>29465</b>
2 x 1.5	16	6.8 - 8.6	29.0	82.0	<b>30207</b>	<b>30205</b>	<b>29484</b>	<b>29485</b>
3 G 1.5	16	7.4 - 9.4	43.0	95.0	<b>30217</b>	<b>30215</b>	<b>29468</b>	<b>29469</b>
4 G 1.5	16	8.4 - 10.5	58.0	117.0	<b>30227</b>	<b>30225</b>	<b>29470</b>	<b>29471</b>
5 G 1.5	16	9.3 - 11.6	72.0	144.0	<b>30237</b>	<b>30235</b>	<b>29472</b>	<b>29473</b>
3 G 2.5	14	9.2 - 11.4	72.0	152.0	<b>30247</b>	<b>30245</b>	<b>29478</b>	<b>29479</b>
4 G 2.5	14	10.1 - 12.5	96.0	192.0	<b>30257</b>	<b>30255</b>	<b>29480</b>	<b>29481</b>
5 G 2.5	14	11.2 - 13.9	120.0	243.0	<b>30267</b>	<b>30265</b>	<b>29482</b>	<b>29483</b>
3 G 4	12	10.5 - 13.1	115.0	235.0	-	-	<b>29825</b>	<b>29826</b>
4 G 4	12	11.5 - 14.3	154.0	300.0	-	-	<b>29488</b>	<b>29489</b>
5 G 4	12	13.0 - 16.1	192.0	361.0	-	-	<b>29490</b>	<b>29491</b>

18.11.2024 / We reserve the right to make technical changes; the imprint in the image is purely exemplary

# H05VV-F / 05VV-F



## 05VV-F

No. cores x cross-sec. mm <sup>2</sup>	AWG, approx.	Outer-Ø min - max mm	Cu factor per km	Weight kg/km, approx.	black	white
					Part no.	Part no.
7 G 1	18	9.3 - 12.0	67.0	131.0	<b>29466</b>	<b>29467</b>
7 G 1.5	16	11.0 - 14.0	101.0	183.0	<b>29474</b>	<b>29475</b>
7 G 2.5	14	13.0 - 17.0	168.0	316.0	<b>29486</b>	<b>29487</b>