1. CONDUCTOR:

1.1 Size and Material: 14 41/30 AWG nickel-plated copper wire.

1.2 O.D.: .072" nom.

2. INSULATION:

2.1 Spiral-wrapped PTFE skived tape.

2.2 One layer of spiral-served fibreglass yarn.

2.3 Braided fibreglass yarn impregnated with a saturant to minimize fraying.

2.4 Marking on the insulation: as per UL and CSA Standards.

2.5 O.D.: .123" nom.

2.6 Color: green with a yellow spiral stripe.

3. PERFORMANCE:

3.1 Voltage rating: 600 VAC R.M.S.

3.2 Temperature rating: 250°C


4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 5256.

4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A/B.

CUSTOMER APPROVAL

| Sign: _ | | | | |
|---------|--|--|--|--|
| Date: | | | | |



A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of

Harbour Industries Canada Limited

A member of The Marmon Group of companies

Prive Garand Done: Date:

April 20, 2006

1365, boul, Industriel, Farnham, Quebec, Canada, J2N 2X3 Verified: Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com Carrio Cote Description: Date: TG600 1441/30N-54 April 20, 2006 Size: Scale: Code Ident. No: Specification No.: Rev. 1 of 1 57104 F00030-54