

# Silicone - Type 3239 25kV

High Voltage Hook-up Wire

UL: 150°C, 25kV



IEWC Part Number	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight	
			in	mm	in	mm	lbs/1k ft	kg/km
<b>3239/24T07S25</b>	24	7	0.062	1.6	0.148	3.8	10	15
<b>3239/22T07S25</b>	22	7	0.062	1.6	0.153	3.9	11	16
<b>3239/20T10S25</b>	20	10	0.062	1.6	0.163	4.1	14	21
<b>3239/18T16S25</b>	18	16	0.062	1.6	0.169	4.3	16	24
<b>3239/16T26S25</b>	16	26	0.062	1.6	0.181	4.6	20	30
<b>3239/14T41S25</b>	14	41	0.062	1.6	0.196	5.0	27	40
<b>3239/12T65S25</b>	12	65	0.062	1.6	0.211	5.4	36	54
<b>3239/10T105S25</b>	10	105	0.062	1.6	0.234	5.9	50	74

## Notes

- Soft-annealed, tinned copper conductor
- Extruded silicone rubber insulation
- RoHS Compliant
- Standard insulation colors: white, black and red

## Applications

For use in electronic and appliance applications. Rated for continuous use up to 150°C.